

Product Display

19、 Electric Scissor Lifts

The product is mainly applied in power, communication, airport, conference and exhibition center, supermarket, factory, station, subway station, etc. CE Certified.



| Model No. | | CPT6 | CPT7.4 |
|-------------------------------------|------|---------------|--------|
| Max. Platform Height | mm | 6000 | 7400 |
| Max. Machine Height | | 7100 | 8500 |
| Min. Platform Height | | 918 | 1020 |
| Ground Clearance | | 80 | |
| Lift Rated Capacity | kg | 300 | 250 |
| Platform Extend Capacity | | 100 | 80 |
| Platform Size | mm | 1870*760*1230 | |
| Platform Extend Length | | 900 | |
| Max. Drive Speed (Platform Stowed) | km/h | 3-4 | |
| Max. Drive Speed(Platform Elevated) | | 0.6-1 | |
| Min. Turning Radius | mm | 1900 | |
| Max. Travel Grade | % | 10-15 | |
| Driving Wheel Size | mm | d250*80 | |
| Caster Size | in | 8 | |
| Driving Motor | v/kw | 2*24/0.4-0.5 | |
| Lifting Motor | | 24/3 | |
| Aneroid Battery | v/Ah | 2*12/120 | |
| Charger | v/A | 24/12 | |
| Pothole Protection System | | Automechanism | |
| Overall Length | mm | 1870 | |
| Overall Width | | 900 | |
| Overall Height | | 2018 | 212 |