



## Product Display

### 43、 Electric Lift Tables

TYPE		ETF30	ETF50	ETFD35	ETFL75
Capacity	kg	300	500	350	750
Max.Table Height	mm	880	1025	1300	970
Min.Table Height	mm	290	440	370	420
The Dimension of Table Size	mm	850x500x50	1010x520x50	910x500x53	1000x510x55
Caster Wheel	mm	Φ 125x40	Φ 150x48	Φ 125x40	Φ 147x50
Overall length	mm	1145	1305	1210	1345
Height Of Handle From The Ground	mm	920	970	920	935
Lifting speed with load/without load	mm/s	65/94	65/94	90/110	70/80
Lowering speed with load/without load	mm/s	98/74	98/74	100/90	50/35
Lifting Cycle(fully charged)		120	100	100	100
Battery x 2		12v21Ah	12v21Ah	12v 24Ah	12v 24Ah
Vertical Travel	mm	590	585	930	550
Lifting Motor(DC24V KW)		0.8	0.8	0.8	0.8
Charger(built-in)24V4A		8.5Hr	8.5Hr	8.5Hr	8.5Hr
Approx Lifting Speed		10	10	10	10
Net Weight	kg	115	157	142	160

Ergonomically designed lifter/transporter features handy hydraulic foot pump to elevate formed-edge platform, reducing strain and fatigue, used for lifting, transporting, positioning, assembling, stacking and unstacking. Easy-to-operate brake keeps unit stationary while loading and unloading, while the lowering valve provides precise lowering.

