



Product Display

47、 Low Profile Lift Table-UY Series

Heavy duty design with larger platform

These tables achieve a low closed height, eliminating the need for a pit installation.

They are manufactured to all European safety standards including EN1570:1999.

Remote power pack with pedestal and controls, protected to IP54.

Upper platform fitted with safety perimeter to prevent descent on contact with obstructions.

24V control box with UP and DOWN buttons and emergency stop.

External power pack equipped with a relief valve against overloading and a compensated flow valve for controlling lowering speed.

Power supply are AC 380V/50HZ/3phase.

Hose burst safety valve to stop the lift table lowering in case of hose breakage.

Removable lifting eyes to facilitate handling and installation of the lift table.

Oiless bushings on pivot points.

Loading ramp is a standard equipment.



Model	Capacity	Platform Size	Min. Height	Max. Height	Stroke	Lifting Time	Power Pack	Net Weight
	(kg)	LXW(mm)	(mm)	(mm)	(mm)	(second)		(kg)
UY1001	1000	1450×1140	85	860	775	25	380V/50HZ, AC 0.75kw	357
UY1002	1000	1600×1140	85	860	775	25		364
UY1003	1000	1450×800	85	860	775	25		326
UY1004	1000	1600×800	85	860	775	25		332
UY1005	1000	1600×1000	85	860	775	25		352
UY1501	1500	1600×800	105	870	775	30	380V/50HZ, AC 1.5kw	367
UY1502	1500	1600×1000	105	870	775	30		401
UY1503	1500	1600×1200	105	870	775	30		415
UY2001	2000	1600×1200	105	870	775	35	380V/50HZ, AC 2.2kw	419
UY2002	2000	1600×1000	105	870	775	35		405