



## Product Display

### 6、Semi-electric Pallet Tuck-TX Series

Model		TX15S		TX15L		TX20S		TX20L	
Capacity	(kg)	1500				2000			
Max. Fork Height	h2 (mm)	205 (or 195)							
Min. Fork Height	h (mm)	85 (or 75)							
Fork Overall Width	m (mm)	520		680		520		680	
Travelling Speed (With Load)	(km/h)	5		5		5		5	
Travelling Speed (Without Load)	(km/h)	6.5		6.5		6.5		6.5	
Overall Height	H (mm)	1310		1310		1310		1310	
Overall Width	W (mm)	730		730		730		730	
Dimension	n (mm)	200		360		200		360	
	h3 (mm)	620		620		620		620	
	Wa (mm)	1350	1500	1350	1500	1350	1500	1350	1500
Overall length	L (mm)	1650	1800	1650	1800	1650	1800	1650	1800
Fork Length	l (mm)	1000	1150	1000	1150	1000	1150	1000	1150
Load Centre	C (mm)	600	650	600	650	600	650	600	650
Load distance	X (mm)	795	945	795	945	795	945	795	945
Wheel Base	Y (mm)	1240	1390	1240	1390	1240	1390	1240	1390
Net Weight (without nattery)	(kg)	215	223	225	233	238	247	248	257
Drive Wheel, Ployurethane		Motor 1200W, Wheel $\varnothing 250 \times 80$ mm							
Battery (service free)	(Ah/V)	80/24							
Battery Charger	(A/V)	8/24							
Traction Battery (option)	(Ah/V)	—				165/24			

Heavy Duty Design  
**Brake system:**Integral electromagnetic disk brake mounted on motor shaft.

**Drive wheel:**complete gear train mounted on ball and roller bearing in oil bath housing. High-torque horizontally mounted motor has coppergraphite brushes for excellent fubrication.

**Load roller:**Tandem Polyurethane.

