



Product Display

13、Electric Stackers-TL Series

The product has passed the CE certification and is mainly applied in petroleum, chemical engineering, pharmacy, light textile, military engineering, painting, coal, port, railroad, warehouse, bridge back, etc. for load and unload, pile and move.

Model No.		TL10-25	TL10-30	TL10-35	TL15-25	TL15-30	TL15-35	TL20-25
Rated Capacity	kg	1000			1500			2000
Load Center		500			400			
Max. Fork Height		2500	3000	3500	2500	3000	3500	2500
Max. Machine Height		2975	3475	3975	2975	3475	3975	3095
Handle Height		1385-1405			1385-1405			
Fork Size	mm	1125*160			1125*160			1125*180
Fork Width		570			570			590
Min. Turning Radius		1700			1750			
Wheel Base		1348			1398			
Front-Wheel Distance		370			320			
Max. Speed Without Load	km/h	4.5-5			5-6			
Max. Speed With Load		3.8-4.2			4-5			
Max. Travel Grade	%	8-10			8-10			
Driving Motor	v/kw	24/1.2			24/1.2-1.3			
Lifting Motor		24/2-3			24/2-3			
Battery	v/Ah	24/240-270			24/240-270			
Charger	v/A	24/30-40			24/30-40			
Overall Length		2040			2040			
Overall Width	mm	856			856			
Overall Height		1770	2020	2270	1770	2020	2270	1890
Overall Net Weight	kg	858	880	900	888	910	930	988

