

TEL:

0086-532-8062-2707



United Material
Handling Technology

1、 Electric Forklift Truck - FN Series

Adopt international advanced design technology, vehicle lines smooth, exciting, up-to-date appearance in line with international trends. According to ergonomics designed to manipulate the handle near the seat, more comfortable operation.

Type	FN05/30	FN075/30	FN10/30
Capacity Q(kg)	500	750	1000
Lifting Height A(mm)	2500-3000		
Load Center F(mm)	400(500)		
Fork Length C(mm)	800-1000		
Control	Site and Steering wheel		
Battery(V/Ah)	DC-24V 6Q-190 、 D-250 、 D-300		
Turning Radius R(mm)	1450	1500	1450
Overall Size L*W*H(mm)	2600*820*1880	2460*820*1880	2624*900*1873
Net.Weight (kg)	1080	1250	1520



E-mail: info@umhandling.com

www.umhandling.com



2、Elecitrc Forklift Truck - EN Series

Frequency Control, hydraulic power steering, driving light; Regenerative braking and mechanical brake system of the double combination of braking and reliable; AC motor, easy maintenance; External fuel tank, wide field of vision door frame, or from stable, the use of safety.

Model		EN10/31
Capacity/rated load	kg	1000
Lift height	mm	3100
Fork width	mm	200-700
Fork Length	mm	800-1000
Speed (laden / unladen)	km/h	6.26/8.0
Load center distance	mm	400
Net weight	kg	1500
Turning radius	mm	1225
The Size	mm	2238×820×1960
Net weight	kg	1500



3、Three Wheel Electric Forklift - FE3R Series

Used to optimize the design of wide field of vision door frame, so that the operation faster and more secure. Before and after the adjustable seats, adjustable steering wheel angle, so that the driver job easy and comfortable. Low height in feet and wide feet and can be provided on, get off at the convenience.

Model		FE3R16AC
Load Capacity /rated load	kg	1600
Load center distance	mm	500
Load distance, centre of drive axle to fork	mm	330
Service Weight ind,battery(see line 6.5)	Kg	2850
Track width,front	mm	848
Lowered mast height	mm	2150
Free lift	mm	145
Lift height	mm	3300
Extended mast height	mm	4220
Overhead load guard height	mm	1980
Coupling height	mm	420
Overall length	mm	3000
Overall width	mm	1017
Fork dimensions	mm	35x100x1150
Fork carriage width	mm	1000
Turning radius	mm	1520
Battery voltage, norminal capacity K5	V/Ah	24/880
Battery weight	kg	676

