



Product Display

11、Semi-electric Stackers-TS Series (Single door frame)

The product has passed the CE certification. It is of one mast structure. It is a half electric forklift for load and unload and short-distance transportation. The operation is very easy. It is reliable. There is no noise and pollution. The malfunction rate is low. It is applicable for the working place with high requirement on load. .

Model No.		TS10-16	TS15-16	TS20-16
Rated Capacity	kg	1000	1500	2000
Load Center	mm	400		
Max. Fork Height		1600		
Fork Length		1000		
Fork Width		300-850		
Min. Turning Radius		1350		
Wheel Base		1180		
Front-Wheel Distance		322		
Lifting Motor		v/kw	12/1.5-1.6	
Aneroid Battery	v/Ah	12/120-150		
Charger	v/A	12/15		
Overall Length	mm	1670		
Overall Width		865		
Overall Height		2060		
Overall Net Weight	kg	340	362	388





Product Display

12、Semi-electric Stackers-TS Series (Double door frame)

The product has passed the CE certification. It is of double mast structure. It is a half electric forklift for load and unload and short-distance transportation. The operation is very easy. It is reliable. There is no noise and pollution. The malfunction rate is low. There are complete specifications for forks to meet the different demands of the customers.

Model No.		TS10-20	TS10-25	TS1030	TS10-35	TS15-20	TS15-25	TS15-30	TS15-35	TS20-20
Rated Capacity	kg	1000				1500				2000
Load Center		400								
Max. Fork Height		2000	2500	3000	3500	2000	2500	3000	3500	2000
Max. Machine Height		2560	3060	3560	4060	2560	3060	3560	4060	2560
Fork Length	mm	1000								
Fork Width		300-850								
Min. Turning Radius		1350			1450	1350		1450		1350
Wheel Base		1185								
Front-Wheel Distance		316								
Lifting Motor	v/kw	12/1.5-1.6								
Aneroid Battery	v/Ah	12/120-150								
Charger	v/A	12/15								
Overall Length	mm	1660								
Overall Width		865		930		865		930		865
Overall Height		1580	183	2080	2330	1580	1830	2080	2330	1580
Overall Net Weight	kg	424	446	468	490	448	470	492	515	460